




TECHNICAL DATA SHEET

NAME	REFERENCE
OPTICAL SENSOR OPERATED HAND DRYER "IBERO" SATIN STAINLESS STEEL	AA92500
DESCRIPTION	
HIGH QUALITY AND PERFORMANCE TRADITIONAL HAND DRYER DOUBLE ELECTRICAL INSULATION OPTICAL SENSOR OPERATED : AUTOMATIC START AND STOP CLASS II: NO GROUNDING WIRE REQUIRED, AT 0,6 mts FROM WATER POINT HIGH QUALITY STAINLESS STEEL SATIN FINISH	
ELECTRICAL SCHEME	
 <p>1. THERMAL FUSE 2. THERMAL CUT-OFF (IN HEATING ELEMENT) 3. HEATING ELEMENT POWER 1800 W 230 V - 50 HZ 4. THERMAL CUT-OFF (IN MOTOR) 5. MOTOR 230 V - 50 HZ 6. ELECTRONIC CIRCUIT 7. OPTICAL SENSOR</p>	EAN CODE 8427950323126

CHARACTERISTICS				
NET (without packaging)	DIMENSIONS (mm)	HEIGHT: 220	WIDTH: 280	DEPTH: 210
	WEIGHT (Kg)	3,655		
GROSS (with packaging)	DIMENSIONS (mm)	HEIGHT: 285	WIDTH: 345	DEPTH: 295
	WEIGHT (Kg)	4,350		
MATERIALS	SATIN STAINLESS STEEL COVER AISI 304 INTERNAL COMPONENTS IN ABS AND POLYCARBONATE"V0" NOZZLE IN CHROME ABS			
COLOUR / FINISH	SATIN STAINLESS STEEL COVER CHROME NOZZLE			
ELECTRICAL FEATURES	VOLTAGE: 230V. AC	AIRSPEED: 121 Km/HOUR		
	FREQUENCY: 50 Hz.	EFFECTIVE AIRFLOW: 300 m ³ /HOUR		
ELECTRICAL FEATURES	CONSUMPTION: 8,8 Amp.	SOUND PRESSURE: 77,5 Db.		
	MOTOR POWER: 200 W.	AIR TEMPERATURE: 54,1 °C (At a distance of 10 cm.)		
ELECTRICAL FEATURES	HEATING ELEMENT POWER: 1800 W.	ELECTRICAL INSULATION: CLASS II		
	TOTAL POWER: 2000 W.	CERTIFICATIONS: TÜV, GS, UL AND CE		
ELECTRICAL FEATURES	MOTOR RPM: 4250	PROTECTION RATIO: IP23		
	TYPE OF MOTOR : BRUSHED			
FIXING	BY MEANS OF FOUR SCREWS AND FOUR WALL PLUGS - PROVIDED			
PACKAGING	SINGLE UNIT PACKAGING	Approved by: Quality Control Dept		
		DATE: 12/05/2015		